

CORRECT

ET



KARAKTERISTIKE	technical data		et 65R	et 75R	et 85R	et 70 RULLI
Radni zahvat	scrubbing width	mm	650	750	820	700
Kapacitet pranja	cleaning capacity up to	m ² /h	3900	4500	4920	4200
Autonomija	operating range	h	4	4	4	4
Rezervoar čiste vode	solution tank capacity	L	110	110	110	110
Rezervoar prljave vode	recovery tank capacity	L	100	100	100	100
Pogon	traction		Anteriore - motoruota / Front - drive wheel / Antérieure - motoroue			
Brzina	forward speed	km/h	0-6	0-6	0-6	0-6
Maksimalni uspon	max. slope	%	7	7	7	7
Vakum	water lift	mbar	145	145	145	145
Pritisak četke	brush pressure	kg	30	30	30	30
Nivo buke	noise level	dB	70	70	70	70
Radijus okretanja	turning radius	mm	1850	1900	1950	1850
VOLTAŽA	voltage		et 65R	et 75R	et 85R	et 70 RULLI
Snaga motora usisivača	vacuum motor		1x550w	1x550w	1x550w	1x550w
Snaga motora četke	brush motor		2x650	2x650	2x650	2x650
Snaga pogonskog motora	traction motor		1x700w	1x700w	1x700w	1x700w
Baterije	baterije		24v 4 x 6v 330Ah	24v 4 x 6v 330Ah	24v 4 x 6v 330Ah	24v 4 x 6v 330Ah
DIMENZIJE	dimensions		et 65R	et 75R	et 85R	et 70 RULLI
Dimenzije	dimensions	mm	1190 x 640 x 1260	1190 x 640 x 1260	1190 x 640 x 1260	1190 x 640 x 1260
Prečnik četke	brush diameter	mm	2 x Ø330	2 x Ø380	2 x Ø410	n° 2 rulli n° 2 cylindr. Ø140 L650
Dužina usisne grane	squeegee width	mm	880	980	1020	980
Težina mašine	machine weight	kg	185	185	190	185
Težina baterije	battery weight	kg	4x40	4x40	4x40	4x40

