

CORRECT

ECOSMART



KARAKTERISTIKE	technical data		ecosmart 55	ecosmart 65
Radni zahvat	scrubbing width	mm	550	650
Kapacitet pranja	cleaning capacity up to	m ² /h	3200	4000
Autonomija	operating range	h	4	3:30
Rezervoar čiste vode	solution tank capacity	L	110	110
Rezervoar prljave vode	recovery tank capacity	L	115	115
Pogon	traction		Anteriore - motoruota Front - Wheel motor	
Brzina	forward speed	km/h	0-6	0-6
Maksimalni uspon	max. slope	%	7	7
Vakum	water lift	mbar	178	178
Pritisak četke	brush pressure	kg	26	35
Nivo buke	noise level	dB	50	50
Radijus okretanja	turning radius	mm	1550	1650
VOLTAŽA	voltage		ecosmart 55	ecosmart 65
Snaga motora usisivača	vacuum motor		750 W	750 W
Snaga motora četke	brush motor		1x 400 W	2x400 W
Snaga pogonskog motora	traction motor		1 x 200 W	1x200 W
Napajanje	voltage		48 Vdc	48 Vdc
Baterije	battery		4 x 12 Vdc x 110 Ah	4 x 12 Vdc x 110 Ah
DIMENZIJE	dimensions		ecosmart 55	ecosmart 65
Dimenzije	dimensions	mm	1186 x 630 x 1220	1186 x 700 x 1220
Prečnik četke	brush diameter	mm	1 x Ø 550 mm	2 x Ø 330 mm
Dužina usisne grane	squeegee width	mm	780	950
Težina mašine	machine weight	kg	130	135
Težina baterije	battery weight	kg	4x26	4x26



Correcto Clean Shop D.O.O.

Svetozara Radojčića 68 B, 11000 Beograd

Tel: +381 60 30 47 197 ; +381 60 40 47 197 ; +381 60 50 47 197

E-mail: office@correcto.rs www.correcto.rs www.correctoshop.rs