

CORRECT

ICM 34-38



KARAKTERISTIKE			technical data	34UE	38UE
Radni zahvat	scrubbing width	mm		850	1000
Kapacitet pranja	cleaning capacity up to	m ² /h		5100	6000
Autonomija	operating range	h		5	5
Rezervoar čiste vode	solution tank capacity	L		190	190
Rezervoar prljave vode	recovery tank capacity	L		180	180
Kapacitet rezervoara za otpad	waste tank capacity	L		/	16
Pogon	traction			TRANSAXLE	TRANSAXLE
Brzina	forward speed	km/h		0-6	0-6
Maksimalni uspon	max. slope	%		12	12
Vakum	water lift	mbar		157	157
Pritisak četke	brush pressure	kg		60	60
Nivo buke	noise level	dB		83	83
Radijus okretanja	turning radius	mm		2750	2750
VOLTAŽA			voltage	34UE	38UE
Snaga motora usisivača	vacuum motor			2 x 850w	2 x 850w
Snaga motora četke	brush motor			2 x 750w	2x750w
Snaga pogonskog motora	traction motor			2 x 500w	2x500w
Napajanje	voltage			36v	36v
Baterije	batteries			1X36v 290Ah	1X36v 290Ah
DIMENZIJE			dimensions	34UE	38UE
Dimenzije	dimensions	mm		1800 x 1050 x 1460	1800 x 1050 x 1460
Prečnik četke	brush diameter	mm		2 x Ø410	3 x Ø360
Dužina usisne grane	squeegee width	mm		1300	1300
Težina mašine	machine weight	kg		385	405
Težina baterije	battery weight	kg		1 X 385	1 X 385
Opciona grupa za čišćenje			optional sweeping group		
Dimenzije	dimensions	mm		600 x 1000 x 440	
Prečnik Centralna četke	central diameter brush	mm		1 x Ø200mm	
Prečnik bočne četke	lateral diameter brush	mm		2 x Ø350mm	
Rezervoar prljave vode	recovery tank capacity	L		L30	
Napajanje	voltage			36V	
Snaga motora četke	brush motor			1 x 510w	
Snaga motora usisivača	vacuum motor			1 x 800w	

