

CORRECT

SP 500



Karakteristika	technical data		SP 500 BT	SP 500 ST
Radni zahvat	scrubbing width	mm	630	630
Kapacitet čišćenje	cleaning capacity up to	m ² /h	2200	2200
Autonomija	operating range	h	3	/
Kapacitet rezervoara za otpad	waste tank capacity	L	35	35
Filter	filter		A cartucce / Cartridge filter	A cartucce / Cartridge filter
Površina za filtriranje	filtering surface	m ² /h	2	2
Brzina	forward speed	km/h	4	4
Maksimalni uspon	max. slope	%	8	8
Nivo buke	noise level	dB	60	75
Voltaža	voltage		SP 500 BT	SP 500 ST
Pogonski motor	traction motor		A cinghia /Belt	A cinghia /Belt
Snaga motora usisivača	vacuum motor		Turbina a flusso libero/ Free-flow turbine	Turbina a flusso libero Free-flow turbine
Napajanje	voltage		12v	/
Verzija	version		battery 1x 12 v 157 Amp/h Opt. 2 x 6v 240 Amp/h	benzina / gasoline
Dimenzije	dimensions		SP 500 BT	SP 500 ST
Dimenzije	dimensions	mm	1245 x 630 x 940	1245 x 630 x 940
Glavna četka	main brush	mm	Ø260 x 500	Ø260 x 500
Bočna četka	side brush	mm	Ø300	Ø300
Težina mašine	machine weight	kg	72	80
Težina baterije	battery weight	kg	38	/

