

CORRECT

ICM 42 - 60



KARAKTERISTIKE	technical data		42 TDB	42 TP /GB	42 TEB
Radni zahvat	scrubbing width	mm	1200	1200	1200
Kapacitet pranja	cleaning capacity up to	mq/h	15000	15000	15000
Autonomija	operating range	h	/	/	8
Rezervoar čiste vode	solution tank capacity	L	260	260	260
Rezervoar prljave vode	recovery tank capacity	L	260	260	260
Kapacitet rezervoara za Otpad	waste tank capacity - optional	L	15	15	15
Jedinica za čišćenje	sweeping unit		Idraulico/Hydraulic	Idraulico/Hydraulic	elettrico / elettric
Pogon	traction		2 Motori idraulici - 2 Hydraulic motors	2 Motori idraulici - 2 Hydraulic motors	2 Motori elettrici - 2 electric motor
Brzina	forward speed	km/h	0-8	0-8	0-6
Maksimalni uspon	max. slope	%	13	13	13
Vakum	water lift	mbar	166	166	166
Pritisak četke	brush pressure	kg	0-150	0-150	0-150
Nivo buke	noise level	dB	85	85	70
Radius okretanja	turning radius	mm	2900	2300	2900
VOLTAŽA	voltage		42 TDB	42 TP /GB	42 TEB
Snaga motora usisivača	vacuum motor		2 x 850 W	2x 850 w	2x 850 W
Snaga motora četke	brush motor		3x OR 80 C Idraulico /Hydraulic	3x OR 80 C Idraulico /Hydraulic	3x750 W
Snaga pogonskog motora	traction motor		2x OP 160 C Idraulico /Hydraulic	2x OP 160 C Idraulico /Hydraulic	2x750 W
Verzija	version		Diesel	benzina /gas	Electric
Punjač za baterije	battery charger		12 V -350 A- 40 Ah	12 V -350 A- 40 Ah	/
Startna baterija	starting battery		/	/	36 V - 80Ah
DIMENZIJE	dimensions		42 TDB	42 TP /GB	42 TEB
Dimenzije	dimensions	mm	2100x1300x1400	2100x1300x1400	2100x1300x1400
Prečnik četke	brush diameter	mm	3x Ø 380	3x Ø 380	3x Ø 380
Dužina usisne grane	squeegee width	mm	1470	1470	1470
Težina mašine	machine weight	kg	850	850	500
Težina baterije	battery weight	kg	/	/	550



KARAKTERISTIKE	technical data		60TEB	I 60 TP /GB	60 TDB
Radni zahvat	scrubbing width	mm	1500	1500	1500
Kapacitet pranja	cleaning capacity up to	m ² /h	15000	15000	18000
Autonomija	operating range	h	8	/	/
Rezervoar čiste vode	solution tank capacity	L	260	260	260
Rezervoar prljave vode	recovery tank capacity	L	260	260	260
Kapacitet rezervoara za Otpad	waste tank capacity - optional	L	15	15	15
Jedinica za čišćenje	sweeping unit		elettrico / elettric	Idraulico/Hydraulic	Idraulico/Hydraulic
Pogon	traction		2 Motori elettrici 2 electric motor	2 Motori idraulici 2 Hydraulic motors	2 Motori idraulici 2 Hydraulic motors
Brzina	forward speed	km/h	0-6	0-8	0-8
Maksimalni uspon	max. slope	%	13	13	13
Vakum	water lift	mbar	166	166	166
Pritisak četke	brush pressure	kg	0-150	0-150	0-150
Nivo buke	noise level	dB	70	85	85
Radius okretanja	turning radius	mm	3020	3020	3200
VOLTAŽA	voltage		60TEB	I 60 TP /GB	60 TDB
Snaga motora usisivača	vacuum motor		2 x 850 W	2x 850 W	2x 850 W
Snaga motora četke	brush motor		3x750 W	3x OR 80 C Idraulico/Hydraulic Hydraulique	3x OR 80 C Idraulico/Hydraulic
Snaga pogonskog motora	traction motor		2x OP 160 C Idraulico Hydraulic	2 x 750 W	2x OP 160 C Idraulico Hydraulic
Verzija	version		electric	benzina/gas	Diesel
Punjač za baterije	battery charger		36 V - 80Ah	/	/
Startna baterija	starting battery		/	12 V -350 A- 40 Ah	12 V -350 A- 40 Ah
DIMENZIJE	dimensions		60TEB	I 60 TP /GB	60 TDB
Dimenzije	dimensions	mm	2100x1300x1400	2100x1300x1400	2100x1300x1400
Prečnik četke	brush diameter	mm	3x Ø 460	3x Ø 460	3x Ø 460
Dužina usisne grane	squeegee width	mm	1650	1650	1650
Težina mašine	machine weight	kg	500	850	850
Težina baterije	battery weight	kg	650	/	/

